

# LOW PROFILE LIFTS

## MORE EFFICIENT PALLETIZING

### TECHNICAL SPECIFICATIONS

**NOTE: EVERYTHING CAN BE CUSTOMIZED FOR YOUR NEEDS**

- > LIFT CAPACITY: FROM 600 - 3000 KG
- > TRAVEL: 545 - 1100 MM.
- > CLOSED HEIGHT: 85 - 105 MM.
- > LENGTH: 1200 - 3000 MM.
- > WIDTH: 800 - 1200 MM.
- > POWER SUPPLY: 3x400 V/50 Hz+PE
- > CE MARKED
- > AVAILABLE IN RAL COLOURS, STAINLESS OR GALVANIZED STEEL, HYGIENIC DESIGN AND ATEX
- > RUNS 10 LIFTS PER HOUR 8 HOURS A DAY (FULL TRAVEL)  
- PLEASE INQUIRE FOR INTENSIVE USE
- > 2 SAFETY LOCKS FOR MAINTENANCE
- > SAFETY TRIP BAR IN ALUMINIUM
- > 2 COMPONENT POLYURETHANE PAINT (RAL)



TRANSLYFT manufactures the highly sought after superlow lifting tables that are used throughout the European industry. Because of the low closed height they are ideal for the handling of goods with fork lift or even a hand pallet truck. You can accessorize with a ramp that further eases the work flow. The low profil lifting tables are ideal for packing lines and palletizing areas.

The standard models come in a closed platform, an U-shaped platform, an E-shaped platform and as a double horizontal solution. They all come with a separate power unit. This type of lifting table can be manufactures in painted, galvanized or stainless steel and in ATEX or Hygienic Design.

See our standard low profile models on the next page or get more info at [www.translyft.com/uk/](http://www.translyft.com/uk/)



Low profile lifting tables can easily be set up as part of a packing line.



The tables can be equipped with different options such as trolley handling.



The low profile lifting tables also come in double horizontal models.

| Type/Capacity kg               | Travel mm | Closed height mm | Total raised height mm | Length mm | Width mm | Lift time sec | Motor kW | Weight kg |
|--------------------------------|-----------|------------------|------------------------|-----------|----------|---------------|----------|-----------|
| TCB 600 K                      | 545       | 85               | 630                    | 1200      | 800      | 11            | 0,75     | 200       |
| TCB 1000                       | 715       | 85               | 800                    | 1500      | 800      | 13            | 0,75     | 260       |
| TCB 1000 F                     | 715       | 85               | 800                    | 1500      | 1000     | 13            | 0,75     | 275       |
| TCB 1000 X                     | 895       | 85               | 980                    | 1500      | 800      | 14            | 1,1      | 240       |
| TCB 1000 XF                    | 895       | 85               | 980                    | 1500      | 1000     | 14            | 1,1      | 260       |
| TCB 1500                       | 715       | 85               | 800                    | 1500      | 800      | 20            | 0,75     | 300       |
| TCB 1500 F                     | 715       | 85               | 800                    | 1500      | 1000     | 20            | 0,75     | 345       |
| TCB 1500 X                     | 895       | 85               | 980                    | 1500      | 800      | 20            | 1,1      | 300       |
| TCB 1500 XF                    | 895       | 85               | 980                    | 1500      | 1000     | 20            | 1,1      | 325       |
| TCB 2000                       | 695       | 105              | 800                    | 1500      | 800      | 20            | 1,1      | 340       |
| TCB 2000 F                     | 695       | 105              | 800                    | 1500      | 1000     | 20            | 1,1      | 360       |
| TCB 600 XL                     | 1100      | 105              | 1205                   | 2000      | 1000     | 27            | 0,75     | 415       |
| TEB 600                        | 715       | 85               | 800                    | 1450      | 900      | 13            | 0,75     | 190       |
| TUB 600 K                      | 545       | 85               | 630                    | 1200      | 1085     | 11            | 0,75     | 180       |
| TUB 1000                       | 715       | 85               | 800                    | 1450      | 1085     | 13            | 0,75     | 235       |
| TUB 1000 X                     | 895       | 85               | 980                    | 1450      | 1000     | 14            | 1,1      | 205       |
| TUB 2000                       | 695       | 105              | 800                    | 1500      | 1200     | 20            | 1,1      | 325       |
| <b>Low - double horizontal</b> |           |                  |                        |           |          |               |          |           |
| TCBH 1200                      | 545       | 85               | 630                    | 2400      | 800      | 22            | 1,1      | 400       |
| TCBH 2000                      | 715       | 85               | 800                    | 3000      | 800      | 27            | 1,1      | 455       |
| TCBH 2000 F                    | 715       | 85               | 800                    | 3000      | 1000     | 27            | 1,1      | 495       |
| TCBH 2000 X                    | 890       | 90               | 980                    | 3000      | 800      | 27            | 1,1      | 415       |
| TCBH 2000 XF                   | 890       | 90               | 980                    | 3000      | 1000     | 27            | 1,1      | 465       |
| TCBH 3000                      | 715       | 85               | 800                    | 3000      | 800      | 40            | 1,1      | 560       |
| TCBH 3000 F                    | 715       | 85               | 800                    | 3000      | 1000     | 40            | 1,1      | 600       |
| TCBH 3000 X                    | 890       | 90               | 980                    | 3000      | 800      | 41            | 1,1      | 510       |
| TCBH 3000 XF                   | 890       | 90               | 980                    | 3000      | 1000     | 41            | 1,1      | 560       |

Separate power unit is standard on the low profile tables.

**Capacity**

Highest load capability (when loaded correctly)

**Travel (1)**

Travel from closed height to top position

**Closed height (2)**

Height at lowest position

**Total raised height (3)**

Height at top position

**Length (4)**

Platform length

**Width (5)**

Platform width

**Lift time**

Time in sec. to top position

**Motor**

Size of motor

**Weight**

Weight of table

