

TROLLEY LIFTER

THE HYGIENIC SOLUTION

TECHNICAL SPECIFICATIONS

NOTE: EVERYTHING CAN BE CUSTOMIZED FOR YOUR NEEDS

- > AVAILABLE IN AISI 304 AND 316
- > LIFT CAPACITY: FROM 1000 - 2000 KG
- > TRAVEL: 820 - 830 MM.
- > CLOSED HEIGHT: 180 - 230 MM.
- > LENGTH: 1400 MM.
- > WIDTH: 1040 MM.
- > POWER SUPPLY: 3x400 V/50 Hz+PE *
(PLEASE INQUIRE FOR OTHER POWER SUPPLY NEEDS)
- > CE MARKED
- > CLEANING MODE FOR BETTER CLEANING OF LIFT (SEE BELOW)
- > WITH OR WITHOUT CLEANING SLOTS
- > HIGHER FOOD SAFETY AFTER CLEANING
- FEWER BACTERIA LEFT ON TABLE (DOCUMENTED EFFECT)
- > AVAILABLE WITH SEMI STAINLESS OR COMPLETELY STAINLESS CYLINDER (VERSION 2 AND 3)
- > RUNS 10 LIFTS PER HOUR 8 HOURS A DAY (FULL TRAVEL)
- PLEASE INQUIRE FOR INTENSIVE USE
- > 2 SAFETY LOCKS FOR MAINTENANCE
- > STAINLESS STEEL SAFETY TRIP BAR WITH OPEN CORNERS THAT ALLOWS FOR BETTER CLEANING

**Significantly better hygiene level
up to 50% savings in terms of
cleaning time and cost**



The TRANSLYFT Hygienic Design for trolleys is a premium stainless steel lifting solution that reassures a better hygiene chain and a more efficient work place. The solution can withstand intensive cleaning.

The cleaning mode makes it possible to raise the platform resulting in more efficient cleaning and a significantly better hygiene level. Consequently, you save both time, water and detergent during the cleaning process (see test result from test in box by above picture).

The TRANSLYFT Hygienic Design trolley lifter can be customized for your needs. Read more about our Hygienic Design at www.translyft.com



The wheel gaps make sure that the trolley does not move when lifting and lowering



The platform can be equipped with slots to further ease the cleaning process.



The lifting table is equipped with ramps to make it easy to roll the trolley on and of the table.

Type/Capacity kg	Travel mm	Closed height mm	Total raised height mm	Length mm	Width mm	Lift time sec	Motor kW	Weight kg
HL 1000 B	830	180	1010	1300	800	18	0.75	175
HL 1000 F	830	180	1010	1300	1000	18	0.75	180
HL 2000	820	230	1050	1300	800	27	0.75	240
HL 2000 F	820	230	1050	1300	1000	27	0.75	250

Hygienic Design standard models. Please quote for other dimensions.

How to get the Trolley lifter in cleaning position



1: The table in top position



2: Run the table down



3: Roll the trolley of



4: Put table in cleaning position



5: Run the table down



6: Ready to clean